


**CARACTERISTIQUES TECHNIQUES**
**BRISE ROCHE HYDRAULIQUE /1700Kg/ 2700Kg/ 3500Kg/ 5000Kg/ 8000Kg**
**PROMOVE XP 101**

	BR1T7	BR2T7	BR3T5	BR5T	BR8T
	1700 Kg	2700Kg	3500Kg	5000 Kg	8000 Kg
Poids	100 Kg	160 Kg	240 Kg	300 Kg	430 Kg
Poids version PB	90 Kg	130 Kg	220 Kg	295 Kg	350 Kg
Hauteur avec outil std	1098 mm	1260 mm	1350 mm	1450 mm	1620 mm
Diamètre outil	42 mm	56 mm	64 mm	80 mm	80 mm
Longueur de travail	260 mm	280 mm	280 mm	420 mm	420 mm
Débit (min/max)	15/25 L/min	15/35 L/min	30/45 L/min	50/75 L/min	60/90 L/min
Pression d'exercice (min/max)	110/130 bar	100/120 bar	110/130 bar	110/140 bar	110/140 bar
Numéro de coups	560/1600 1/min	600/1380 1/min	700/1250 1/min	480/900 1/min	540/860 1/min
Energie par coup max	200 J	290 J	425 J	870 J	1020 J
Poids de la pelle (min/max)	1/2 50 t	1 80/4 t	3/5 20 t	4/9 t	5 5/10 t
Connexion flexible d'envoi	1/2 in	1/2" in	3/4" in	3/4" in	3/4" in
Connexion flexible de retour	1/2 in	1/2" in	3/4" in	3/4" in	3/4" in
Contrpression max	25 bar	25 bar	25 bar	25 bar	25 bar


**Renseignements et Réservation sur :**  
**[hl-btp.fr](http://hl-btp.fr)**
**N° Tel. 04 76 91 00 47**